

Fork Slot Truss Jibs

Fork Slot Truss Jib - Attachments jibs could be used on extendable-reach lift trucks, rough terrain straight-mast forklifts or also on industrial forklifts. The forklift jib cranes could be fitted onto the forklift through inserting both of the forks into the fork pockets. The back of the jib crane then seats towards the rear of the fork and a security chain wraps the forklift carriage to hold it into position.

Jib Boom Forklift Attachment Load Capacity

The load capacity of a forklift jib has a maximum of around 1935 pounds up to 6000 lbs on either the extended or retracted positions range. You might need to consult with a material handling specialist concerning the particular limits of your lift truck application. The load capacity rankings are really for the jib itself and not the lift truck or even the maximum load that could be handled safely using a particular forklift. It is essential to bear in mind that at any time when any accessories like for instance a forklift jib are attached to the forklift, the new center of gravity created by the accessory will reduce the overall lift capability of the forklift. There are guidelines available that offer information on the way to properly estimate these load limits.

Before utilizing whichever lift truck jib, make sure that the hooks and shackles are correctly secured to the lift truck. Verify and also double check that the pins are tight. It is very important that the load calculations have been correctly done and double checked. Keep in mind to take into account the truth that rated capacities sometimes decrease when the boom is in an elevated position, every time the boom is fully extended with telehandlers or every time the mast is tilted forward.